

Trust-aware State Estimation Under False Data Injection in Distributed Sensor Networks

Shanshan Zheng, Tao Jiang, John S. Baras
Institute for Systems Research
Department of Electrical and Computer Engineering
University of Maryland, College Park, MD, 20742
Email: {sszheng,tjiang,baras}@umd.edu

Abstract—Distributed sensor networks have been widely employed to monitor and protect critical infrastructure assets. The network status can be estimated by centralized state estimation using coordinated data aggregation or by distributed state estimation, where nodes only exchange information locally to achieve enhanced scalability and adaptivity to network dynamics. One important property of state estimation is robustness against false data injection from sensors compromised by attackers. Different from most existing works in the literature that focus on centralized state estimation, we propose two novel robust distributed state estimation algorithms against false data injection. They are built upon an existing distributed Kalman filtering algorithm. In the first algorithm, we use variational Bayesian learning to estimate attack parameters and achieve performance similar to a centralized majority voting rule, without causing extra communication overhead. In the second algorithm, we introduce heterogeneity into the network by utilizing a subset of pre-trusted nodes to achieve performance better than majority voting. We show that as long as there is a path connecting each node to some of the pre-trusted nodes, the attackers can not subvert the network. Experimental results demonstrate the effectiveness of our proposed schemes.

I. INTRODUCTION

A distributed sensor network consists of a set of spatially scattered sensors that can measure various properties of the environment, formulate local and distributed inferences, and make responses to events or queries [1]. It can be deployed to monitor and protect critical infrastructure assets, such as power grids, automated railroad control, water and gas distribution, etc. However, due to the unattended operating environment of sensor networks, it is possible for an attacker to compromise sensors to introduce malicious measurements, which we call *false data injection*. The false measurements can affect the outcome of state estimation and mislead the system into making wrong decisions.

Detecting and purging false measurements injected by compromised nodes is a challenging research problem in sensor networks. The energy and cost constraints restrict the deployment of tamper resistant hardware for the whole network. Once a node is compromised, all the security information stored in the node will be exposed to the attackers. The normal nodes cannot distinguish the attackers by only using cryptographic techniques. Most existing works use *majority voting* based schemes to prevent the false data injection attack. Ye et al. [2] presented a statistical en-route filtering mechanism in which the truthfulness of data from each node is determined via collective decision-making by multiple nodes. In [3], Shukla et al. presented a secure statistical scheme to distinguish data transience from false injection in a clustered sensor network

by utilizing statistical digests sent from each sensor. For additional results see [4]–[6]. However, all these works rely on a hierarchical architecture and central coordination among sensors, which limits sensor network’s scalability due to the large number of nodes and the volatility of the network.

In this paper, we focus on robust *distributed state estimation* against false data injection, where each node in the network tries to estimate the states as accurately as possible, by using only local information. Under this setting, how to utilize *majority voting* is not obvious. If each node reports its data to all nodes, the network will be congested by the large communication overhead. We propose a distributed state estimation method with Bayesian learning, which achieves performance similar to a centralized majority voting rule without causing extra communication overhead. One limitation of using majority voting is that the network may be totally subverted when more than half of the sensors are compromised. To overcome this problem, we introduce heterogeneity into the network through a subset of pre-trusted nodes. We proposed a trust-aware state estimation scheme which can propagate trust from the pre-trusted nodes to other nodes. We show that as long as there is a path connecting every node to some of the pre-trusted nodes, the attacker cannot subvert the network even when more than half of the sensors are compromised.

The rest of the paper is organized as follows. Section II gives the formulation of the problem. Then we describe our Bayesian learning based scheme and trust-aware scheme in Sections III and IV, respectively. Section V presents conclusions and future work.

II. PROBLEM FORMULATION

We consider a sensor network composed of n sensors, which is used for state estimation of a linear random process $\mathbf{x}(k+1) = A\mathbf{x}(k) + \mathbf{w}(k)$. $\mathbf{x}(k) \in R^m$ is the state vector, $\mathbf{w}(k) \in R^m$ is the state noise, which accounts for modeling errors, uncertainties or perturbations to the process and is assumed to be Gaussian with 0 mean and covariance matrix Q . The initial state \mathbf{x}_0 has a Gaussian distribution with mean $\boldsymbol{\mu}_0$ and covariance matrix M_0 . We assume each sensor can sense this process and the sensing model for each sensor is given by $\mathbf{y}_i(k) = H_i\mathbf{x}(k) + \mathbf{v}_i(k)$, where $\mathbf{y}_i(k) \in R^{p_i}$ is the observation made by sensor i , and $\mathbf{v}_i(k) \in R^{p_i}$ is the measurement noise, assumed to be Gaussian with zero mean and covariance V_i . In distributed sensing, the measurements of an individual sensor may only contain partial information of the state, so state estimation requires the cooperation of sensors in the network.

In distributed state estimation, the goal of each sensor is to compute an accurate estimation of the state $\mathbf{x}(k)$ using its local measurements and the information received from its communication neighbors. Distributed Kalman Filtering (DKF) provides a solution for this problem. The main idea of DKF [7] is to use a standard Kalman filter locally, together with a consensus step to ensure that the local estimates agree. However, existing DKF algorithms are derived in a benign setting without considerations of possible malicious attacks. Therefore they are not robust against false data injection. In what follows, we use the DKF algorithm introduced in [7] as a basic algorithm to build our robust distributed estimation algorithms. Let $G = (\mathcal{V}, \mathcal{E})$ be a graph with an adjacency matrix $[g_{ij}]$ that specifies the topology of the sensor network, and $\mathcal{N}_i = \{j \in \mathcal{V} | g_{ij} \neq 0\}$ be the communication neighborhood of sensor i . Let $\mathcal{J}_i = \mathcal{N}_i \cup \{i\}$ denote the inclusive neighbors of node i and $\mathbf{y}(k) = [\mathbf{y}_1(k), \dots, \mathbf{y}_n(k)]^T$ denote the measurements obtained at all sensors by time k . Then given the observations $\mathbf{y}(1:k) = \{\mathbf{y}(1), \dots, \mathbf{y}(k)\}$, we denote the state estimates at node i as follows

$$\hat{\mathbf{x}}_i(k) = \mathbb{E}[\mathbf{x}(k) | \mathbf{y}(1:k)], \quad \bar{\mathbf{x}}_i(k) = \mathbb{E}[\mathbf{x}(k) | \mathbf{y}(1:k-1)],$$

$$\hat{M}_i(k) = \text{Cov}(\mathbf{x}(k) | \mathbf{y}(1:k)), \quad \bar{M}_i(k) = \text{Cov}(\mathbf{x}(k) | \mathbf{y}(1:k-1)).$$

The basic algorithm is described in Algorithm I, where ϵ is a small positive constant. For simplicity, we omitted the time index. In each round, node i only needs to broadcast the message $(\mathbf{u}_i, U_i, \bar{\mathbf{x}}_i)$ to its neighboring nodes.

Algorithm I: Basic DKF Algorithm [7]

1. Initialization: $M_i = M_0, \bar{\mathbf{x}}_i = \boldsymbol{\mu}_0$
 2. While new data exists do
 3. Locally aggregate data and covariance matrices:

$$\forall j \in \mathcal{J}_i, \mathbf{u}_j = H_j^T V_j^{-1} \mathbf{y}_j, \mathbf{z}_i = \sum_{j \in \mathcal{J}_i} \mathbf{u}_j,$$

$$U_j = H_j^T V_j^{-1} H_j, S_i = \sum_{j \in \mathcal{J}_i} U_j$$
 4. Compute the Kalman-consensus estimate:

$$\hat{M}_i = (\bar{M}_i^{-1} + S_i)^{-1},$$

$$\hat{\mathbf{x}}_i = \bar{\mathbf{x}}_i + \hat{M}_i(\mathbf{z}_i - S_i \bar{\mathbf{x}}_i) + \epsilon \hat{M}_i \sum_{j \in \mathcal{N}_i} (\bar{\mathbf{x}}_j - \bar{\mathbf{x}}_i)$$
 5. Update the state of the Kalman-consensus filter:

$$\bar{M}_i = A \hat{M}_i A^T + Q, \quad \bar{\mathbf{x}}_i = A \hat{\mathbf{x}}_i$$
 6. end while
-

Next we introduce the threat model for false data injection. Let \mathbf{y}^a represent the vector of measurements that may contain malicious data, i.e., $\mathbf{y}^a(k) = \mathbf{y}(k) + \mathbf{a}(k)$, where $\mathbf{a}(k) = [\mathbf{a}_1(k), \dots, \mathbf{a}_n(k)]^T$ is the malicious data added to the original measurements. We call $\mathbf{a}(k)$ the *attack vector*. The i^{th} element of $\mathbf{a}(k)$ being non-zero means that the attacker compromises the i^{th} sensor and replaces its original measurement $\mathbf{y}_i(k)$ with a false measurement $\mathbf{y}_i(k) + \mathbf{a}_i(k)$. The attacker can choose any arbitrary vector as the attack vector $\mathbf{a}(k)$. It's easy to see that even if only one sensor is compromised, the state estimation $\hat{\mathbf{x}}^a(k)$ under the false data injection can deviate from the true state $\mathbf{x}(k)$ arbitrarily or be arbitrarily noisy.

III. DKF WITH BAYESIAN LEARNING

The basic idea of our DKF algorithm with Bayesian learning is to use Bayesian learning to estimate the attack vector and then try to remove the effects of the estimated attack vector from the measurements. Since Bayesian learning usually involves highly complicated computational techniques such as Markov Chain Monte Carlo, and the resource constraints in

a sensor network requires algorithms to be fast and computationally efficient, we propose to use variational Bayesian learning [8], which is an approximate but efficient method for estimating the marginal likelihood of probabilistic models with latent variables or incomplete data.

a) *DKF with variational Bayesian learning*: In the DKF model, the latent variables are the system states to be estimated: $\mathbf{x}(1:k) = \{\mathbf{x}(1), \dots, \mathbf{x}(k)\}$, and the observations are the malicious measurements $\mathbf{y}^a(1:k) = \{\mathbf{y}^a(1), \dots, \mathbf{y}^a(k)\}$. In general, the attack vector can be modeled by a Gaussian mixture model (GMM), as GMM comprises a finite or infinite number of different Gaussian distributions that can describe different features of data. To simplify the problem and focus on the performance of the algorithm, we assume the attack vector is drawn from a single multi-variate Gaussian distribution with parameters $\boldsymbol{\mu}^a$ and V^a and the attack signals at each sensor are uncorrelated, so V^a is a block-wise diagonal matrix. Let $\hat{V} = \text{diag}(V_1 + V_1^a, \dots, V_n + V_n^a)$ and denote the model parameters by $\boldsymbol{\theta} = \{\boldsymbol{\mu}^a, \hat{V}\}$, the marginal likelihood of the model can be expressed by

$$f(\mathbf{y}^a(1:k)) = \int \prod_{i=1}^n f(\mathbf{y}_i^a(1:k) | \mathbf{x}(1:k), \boldsymbol{\theta}) f(\mathbf{x}(1:k)) f(\boldsymbol{\theta}) d\mathbf{x} d\boldsymbol{\theta}.$$

Denoting the Gaussian distribution by $N(\cdot)$, we have

$$f(\mathbf{y}_i^a(1:k) | \mathbf{x}(1:k), \boldsymbol{\theta}) = \prod_{j=1}^k N(H_i \cdot \mathbf{x}(j) + \boldsymbol{\mu}_i^a, \hat{V}_i),$$

$$f(\mathbf{x}(1:k)) = \prod_{j=1}^k N(A \cdot \mathbf{x}(j-1), Q).$$

Furthermore, we assume that $\boldsymbol{\mu}^a$ and \hat{V} have conjugate priors, so the posterior probability distribution of $\boldsymbol{\theta}$ will be in the same family as the prior probability distribution, i.e.,

$$\boldsymbol{\mu}^a | (\boldsymbol{\mu}^0, \rho^0, \hat{V}) \sim N(\boldsymbol{\mu}^0, \hat{V} / \rho^0), \quad \hat{V}^{-1} | (\gamma^0, B) \sim W(\gamma^0, B^{-1} / \gamma^0),$$

where $\boldsymbol{\mu}^0, \rho^0, \gamma^0$ and B are hyper-parameters and $W(\cdot)$ represents the Wishart distribution. Since the distributions $f(\mathbf{y}^a(1:k)), f(\mathbf{x}(1:k))$ and $f(\boldsymbol{\theta})$ all belong to the exponential family, following the theorem in [8] for variational Bayesian learning, we can obtain the updating rules for the attack parameters $\tilde{\boldsymbol{\mu}}_i^a = \mathbb{E}[\boldsymbol{\mu}_i^a | \mathbf{y}(1:k)]$ and $\tilde{V}_i(k) = \mathbb{E}[\hat{V}_i | \mathbf{y}(1:k)]$ as shown in (1) and (2). For simplicity, we assume B is diagonal, that is, we assume the measurement noise is uncorrelated in each dimension.

$$\tilde{\boldsymbol{\mu}}_i^a(k) = \frac{\rho^0 \boldsymbol{\mu}_i^0 + \sum_{j=1}^k [\mathbf{y}_i(j) - H_i \cdot \hat{\mathbf{x}}_i(j)]}{\rho^0 + k}, \quad (1)$$

$$\tilde{V}_i(k) = \frac{[\text{diag}(\rho^0 \boldsymbol{\mu}_i^0 + \sum_{j=1}^k \mathbf{y}_i(j) - H_i \hat{\mathbf{x}}_i(j))]^2 + \gamma^0 B_i}{\gamma^0 + k}$$

$$+ \frac{\rho^0 \cdot [\text{diag}(\boldsymbol{\mu}_i^0)]^2 + \sum_{j=1}^k [\text{diag}(\mathbf{y}_i(j) - H_i \hat{\mathbf{x}}_i(j))]^2}{\gamma^0 + k}, \quad (2)$$

where $\text{diag}(\mathbf{v})$ represents a diagonal matrix whose diagonal entries are the components of the vector \mathbf{v} . Equations (1) and (2) require all data until time k , so they cannot be computed online. We rewrite them in a form using only current observed values, as described in Algorithm II. Algorithm II represents our DKF algorithm with variational Bayesian learning.

To evaluate the performance of Algorithm II, we use it to estimate the position of a moving object in R^2 that approximately moves in circles. The sensor networks used in our experiments are comprised of 100 randomly located nodes.

Algorithm II: DKF Algorithm with Bayesian Learning

1. Initialization: $M_i = M_0$, $\bar{\mathbf{x}}_i = \boldsymbol{\mu}_0$, $V = B$,
 $\bar{\boldsymbol{\mu}}^a = \boldsymbol{\mu}^0$, $\rho = \rho^0$, $\gamma = \gamma^0$
 2. While new data exists do
 3. Locally aggregate data and covariance matrices:
 $\forall j \in \mathcal{J}_i$, $\mathbf{u}_j = H_j^T \bar{V}_j^{-1} (\mathbf{y}_j^a - \bar{\boldsymbol{\mu}}_j^a)$, $\mathbf{z}_i = \sum_{j \in \mathcal{J}_i} \mathbf{u}_j$,
 $U_j = H_j^T \bar{V}_j^{-1} H_j$, $S_i = \sum_{j \in \mathcal{J}_i} U_j$
 4. Compute the Kalman-consensus estimate:
 $\hat{M}_i = (\bar{M}_i^{-1} + S_i)^{-1}$,
 $\hat{\mathbf{x}}_i = \bar{\mathbf{x}}_i + \hat{M}_i (\mathbf{z}_i - S_i \bar{\mathbf{x}}_i) + \epsilon \hat{M}_i \sum_{j \in \mathcal{N}_i} (\bar{\mathbf{x}}_j - \bar{\mathbf{x}}_i)$
 5. Compute the attack parameter estimate:
 $\tilde{\boldsymbol{\mu}}_i^a = (\rho \bar{\boldsymbol{\mu}}_i^a + \mathbf{y}_i^a - H_i \hat{\mathbf{x}}_i) / (\rho + 1)$,
 $\tilde{V}_i = (\gamma \bar{V}_i + \rho [\text{diag}(\bar{\boldsymbol{\mu}}_i^a)]^2 - (\rho + 1) [\text{diag}(\tilde{\boldsymbol{\mu}}_i^a)]^2 +$
 $[\text{diag}(\mathbf{y}_i - H_i \hat{\mathbf{x}}_i)]^2) / (\gamma + 1)$
 6. Update the state of the Kalman-consensus filter:
 $\bar{M}_i = A \hat{M}_i A^T + Q$, $\bar{\mathbf{x}}_i = A \hat{\mathbf{x}}_i$, $\rho = \rho + 1$,
 $\gamma = \gamma + 1$, $\bar{\boldsymbol{\mu}}_i^a = \tilde{\boldsymbol{\mu}}_i^a$, $\bar{V}_i = \tilde{V}_i$
 7. end while
-

There are two main observations. First, the algorithm is very robust under attacks that have $\boldsymbol{\mu}^a = \mathbf{0}$. No matter what is the value of V^a and how many sensors are compromised, as long as there is one sensor not compromised, the network always gives accurate estimations. Second, the algorithm performs as *majority voting* when $\boldsymbol{\mu}^a \neq \mathbf{0}$, as we can see in Figure 1. The




Fig. 1: Performance of Algorithm II

performance is very good when 45 sensors are compromised, but degrades abruptly when 55 sensors are compromised. The attack parameters in Figure 1 are set as $\boldsymbol{\mu}_i^a = [10, 10]$ and $V^a = 0$. The reason for the two observations is that in Algorithm II nodes use all the data received for estimation and resolve the inconsistency among data by adjusting the estimated mean and covariance matrix of the measurement noise. When $\boldsymbol{\mu}^a = \mathbf{0}$, the algorithm handles the perturbation on the covariance matrix well since it knows that large noise covariance matrix indicates low accuracy. But when the perturbation is on the mean value, the algorithm cannot identify compromised nodes and only the majority voting rule can be used.

IV. TRUST-AWARE DISTRIBUTED KALMAN FILTERING

In this section, we propose a trust-aware scheme for DKF and show that it is robust under false data injection even when the majority of nodes are compromised. We introduce a subset of pre-trusted nodes into the network, which are special nodes

that can be highly trusted, e.g., sensors equipped with tamper resistant hardware. We show that as long as there is a path connecting every node in the network to some of the pre-trusted nodes, the attacker can not subvert the system.

a) *Computational Model for Trust*: To handle the uncertainty on the possible existence of malicious nodes, we assume that each node is in one of two states: normal or malicious. We denote the state space by $\mathcal{S} = \{S_1, S_2\}$, where S_1 is the normal state and S_2 is the malicious state, and denote the true state of node i by $S(i)$. Then the local trust opinion of node i on node j is defined by the transition probability matrix:

$$P_{i,j} = \begin{bmatrix} \Pr(S(i) = S_1 | S(j) = S_1) & \Pr(S(i) = S_1 | S(j) = S_2) \\ \Pr(S(i) = S_2 | S(j) = S_1) & \Pr(S(i) = S_2 | S(j) = S_2) \end{bmatrix}.$$

$P_{i,j}$ is a column stochastic matrix, i.e., the sum of each column is equal to 1. The computation of $P_{i,j}$ depends on the particular application. As our first step for the design, we model $P_{i,j}$ by a logistic function that depends on the Euclidean distance between the measurements from two neighboring nodes. We assume neighboring nodes have the same observation matrix H_i , so the larger the distance between the measurements, the smaller the trust the nodes have for each other. More general assumptions on H_i can be made and may require different models for $P_{i,j}$; we will explore this issue in the future. Let i and j be neighbors that exchange measurements $\mathbf{y}_i^a(k)$ and $\mathbf{y}_j^a(k)$ at the k th step, and denote $d_{ij}(k) = \|\mathbf{y}_i^a(k) - \mathbf{y}_j^a(k)\|_2$. We compute the conditional probability by

$$P_{ij}(1, 1) = P_{ij}(2, 2) = f(\mathbf{y}_i^a(k), \mathbf{y}_j^a(k)) = \frac{2e^{-d_{ij}(k)/\alpha}}{1 + e^{-d_{ij}(k)/\alpha}},$$

The reason we set $P_{ij}(1, 1) = P_{ij}(2, 2)$ is that there is no prior information about the normal state and malicious state, so we treat the two cases as equally likely. The function $f(\mathbf{y}_i^a(k), \mathbf{y}_j^a(k))$ is actually a ‘soft’ step function, i.e., when $d_{ij}(k) = 0$, it equals to 1 and when $d_{ij}(k) = +\infty$, it equals to 0. The parameter α controls the slope and cutoff value of the function. To accumulate previous experience into the local trust opinion, we update the matrix $P_{i,j}(k)$ by

$$P_{i,j}^{(k)} = (1 - \beta) \begin{bmatrix} f(\mathbf{y}_i^a(k), \mathbf{y}_j^a(k)) & 1 - f(\mathbf{y}_i^a(k), \mathbf{y}_j^a(k)) \\ 1 - f(\mathbf{y}_i^a(k), \mathbf{y}_j^a(k)) & f(\mathbf{y}_i^a(k), \mathbf{y}_j^a(k)) \end{bmatrix} + \beta P_{i,j}^{(k-1)}$$

where β is a time discount factor.

The global trust value for node i is defined to be a 2×1 vector \mathbf{g}_i , which represents the probability of node i in one of the two states, i.e.,

$$\mathbf{g}_i = [\Pr(S(i) = S_1), \Pr(S(i) = S_2)]^T.$$

Given node j 's global trust value, node i 's posterior probability in one of the two states can be computed by $P_{i,j} \cdot \mathbf{g}_j$. Assuming a uniform prior for node i 's neighboring nodes, the estimate of the posterior probability of i can be written as

$$\mathbf{g}_i = \frac{1}{|\mathcal{N}_i|} \sum_{j \in \mathcal{N}_i} P_{i,j} \cdot \mathbf{g}_j.$$

Since the global trust values for the pre-trusted nodes are known, we propagate the global trust from them to other nodes in the network. Denote the set of indices of the pre-trusted nodes by \mathcal{T} and the set of indices of other nodes by \mathcal{U} . Without loss of generality, we assume the pre-trusted nodes are indexed from 1 to t . Let $\mathbf{g}_{\mathcal{T}} = [\mathbf{g}_1, \dots, \mathbf{g}_t]^T$, $\mathbf{g}_{\mathcal{U}} = [\mathbf{g}_{t+1}, \dots, \mathbf{g}_n]^T$, $D_{\mathcal{U}\mathcal{U}} = \text{diag}(|\mathcal{N}_{t+1}|, \dots, |\mathcal{N}_n|)$, and $P_{\mathcal{U}\mathcal{U}}$ be the transition probability matrix from \mathcal{U} to \mathcal{U} , i.e., $P_{\mathcal{U}\mathcal{U}}(i, j) = P_{t+i, t+j}$,

$P_{\mathcal{U}\mathcal{T}}$ be the transition probability matrix from \mathcal{U} to \mathcal{T} , i.e., $P_{\mathcal{U}\mathcal{T}}(i, j) = P_{t+i, j}$. Then the computation of the global trust values for nodes in \mathcal{U} can be written in a matrix form, i.e.,

$$D_{\mathcal{U}\mathcal{U}} \cdot \mathbf{g}_{\mathcal{U}} = P_{\mathcal{U}\mathcal{U}} \cdot \mathbf{g}_{\mathcal{U}} + P_{\mathcal{U}\mathcal{T}} \cdot \mathbf{g}_{\mathcal{T}}. \quad (3)$$

Since $D_{\mathcal{U}\mathcal{U}}^{-1}P_{\mathcal{U}\mathcal{U}}$ is a sub stochastic matrix, it can be proved [9] that if for every node $i \in \mathcal{U}$, there exists a path that connects some node $j \in \mathcal{T}$ to i , then the spectral radius $\rho(D_{\mathcal{U}\mathcal{U}}^{-1}P_{\mathcal{U}\mathcal{U}})$ is less than 1 and the following Jacobi iteration converges to the unique solution of equation (3),

$$\forall i \in \mathcal{U}, \mathbf{g}_i^{(k+1)} = \frac{1}{|\mathcal{N}_i|} \left[\sum_{j \in \mathcal{U}, j \in \mathcal{N}_i} P_{i,j} \mathbf{g}_j^{(k)} + \sum_{l \in \mathcal{T}, l \in \mathcal{N}_i} P_{i,l} \mathbf{g}_l \right]. \quad (4)$$

The convergence speed of equation (4) depends on the graph structure. More specifically, it is related to the second largest eigenvalue of the matrix $D_{\mathcal{U}\mathcal{U}}^{-1}P_{\mathcal{U}\mathcal{U}}$ [10]. Experimental results show that this computation converges very fast, usually in less than 10 iterations. The reason for the fast convergence is discussed in [10].

To handle the convergence of the distributed Kalman filtering and the trust propagation process together, we evaluate trust in a smaller time scale than the DKF. That is, we let the trust propagation algorithm achieve convergence between each interval of state updates in DKF. This is possible since equation (4) converges very fast. Moreover, since an abrupt change to a node's trust value does not occur frequently, we can expect that after the first trust evaluation, the following ones will converge much faster. Let $r_i = 1 \times \mathbf{g}_i(1) + 0 \times \mathbf{g}_i(2)$ be the trust weight of node i , which is the probability that node i is in the normal state, Figure 2 illustrates the performance of the trust evaluation algorithm on distinguishing malicious nodes from normal nodes. We can see that the trust weights




Fig. 2: Distribution of trust weights for nodes in the network for the normal nodes are always larger than 0.5, while the malicious nodes always have trust weights less than 0.5.

b) *Trust-aware DKF algorithm:* After trust propagation, the DKF algorithm can weight the data sent by a node by its trust weight r_i so less trusted nodes have less impact on the algorithm. We can also isolate those less trusted nodes by ignoring data sent by them. In this way, the algorithm can achieve better performance. We name the algorithm with trust weight as Algorithm III and the algorithm of isolating less-trusted nodes as Algorithm IV. Table I shows the performance of algorithm III, IV, and the DKF algorithm with Bayesian learning when 60 randomly selected sensors are compromised. We measure the algorithm performance by the mean square error till time k , i.e., $e_i^{MSE} = \sqrt{(\sum_{l=1}^k (\hat{\mathbf{x}}_i(l) - \mathbf{x}(l))^2)/k}$, where $\hat{\mathbf{x}}_i(l)$ is the state estimate by sensor i at time l . In

the experiment, we set $k = 400$. Since the sensors can approximately achieve consensus in DKF [7], the estimated state $\hat{\mathbf{x}}_i(l)$ is approximately the same for each sensor i , and so is the value of e_i^{MSE} .

TABLE I: Performance Comparison of Algorithm II, III, IV

μ_i^a, V_i^a	[5, 5], 0	[5, 5], 2	[10, 10], 0	[10, 10], 5
Algorithm II	4.7345	3.1572	9.8317	6.8935
Algorithm III	1.2816	1.6131	3.3624	2.1507
Algorithm IV	0.6724	0.5298	1.1997	0.8966

We can see that the trust-aware schemes perform better than the DKF algorithm with Bayesian learning, and Algorithm IV performs better than Algorithm III. The only drawback of Algorithm IV is that the isolation of the less-trusted nodes may lead to a disconnected network. Also we observe that when $V_i^a \neq 0$, the algorithms may perform better than the case when $V_i^a = 0$, which means that V_i^a being non-zero in some sense reduces the impact of μ_i^a on the estimated states.

V. CONCLUSIONS

We proposed two schemes for robust state estimation in distributed sensor networks against false data injection. The first scheme is based on variational Bayesian learning, which achieves good performance as a majority voting rule without causing extra communication overhead. The second scheme achieves performance better than majority voting by introducing a subset of pre-trusted nodes into the network. Experimental results demonstrate the effectiveness of our schemes. In future work, we will further investigate our trust-aware scheme, e.g., different models for the probability transition matrix $P_{i,j}$, the impact of the number of pre-trusted nodes and their positions on the performance of the trust-aware scheme.

ACKNOWLEDGEMENTS

Research supported by the Defense Advanced Research Projects Agency (DARPA) under award number 013641-001 for the Multi-Scale Systems Center (MuSyC), through the FRCP of SRC and DARPA, and by US Air Force Office of Scientific Research MURI award FA9550-09-1-0538.

REFERENCES

- [1] K. Pratik and H. Sajid, "Special issue on information fusion in distributed sensor networks," *Information Fusion*, 2008.
- [2] F. Ye, H. Luo, S. Lu, and L. Zhang, "Statistical en-route filtering of injected false data in sensor networks," in *Proceedings of IEEE INFOCOM*, 2004.
- [3] V. Shukla and D. Qiao, "Distinguishing data transience from false injection in sensor networks," in *SECON 2007*, 2007.
- [4] Y. Zhang, J. Yang, and H. Yu, "Interleaved authentication for filtering false reports in multipath routing based sensor networks," in *Proceedings of IEEE IPDPS*, 2006.
- [5] Z. Yu and Y. Guan, "A dynamic en-route scheme for filtering false data injection in wireless sensor networks," in *Proceedings of IEEE INFOCOM*, 2006.
- [6] B. Przydatek, D. Song, and A. Perrig, "SIA: Secure information aggregation in sensor networks," in *Proceedings of ACM Sensys.*, 2003.
- [7] R. Olfati-Saber, "Distributed Kalman filtering for sensor networks," in *Proceedings of IEEE Conference on Decision and Control*, 2007.
- [8] M. J. Beal and Z. Ghahramani, "The variational Bayesian EM algorithm for incomplete data: with application to scoring graphical model structures," *Bayesian Statistics*, 2003.
- [9] O. Chapelle, B. Scholkopf, and A. Zien, *Semi-Supervised Learning*. MIT Press, 2006.
- [10] T. H. Haveliwala, S. D. Kamvar, and A. D. Kamvar, "The second eigenvalue of the Google matrix."